

# THIBAUT

WIDE WIDTH PERFORMANCE

## Care & Cleaning of Thibaut Performance Wide Width Fabrics

### FADE-RESISTANCE

Solution dyed acrylic fabrics are unmatched in resistance to fading and the degrading effects of sunlight. These performance characteristics are inherent to the fabric.

### LIMITED FIVE YEAR WARRANTY

Our five year limited warranty guarantees our fabric for use in normal conditions including sunlight, salt and weather exposure. Coverage includes:

- Significant loss of color
- Degradation / lose of strength

It does not cover misuse, abuse, or pilling

### CLEANING CODE = W S B

Fabrics are cleanable with water-based detergents, solvents and bleach.

### GENERAL CLEANING FOR THIBAUT OUTDOOR PERFORMANCE FABRICS

We recommend vacuuming regularly with an upholstery attachment, since dust and dirt cause fabric to wear more quickly.

- An annual professional cleaning will keep your drapery looking its best.
- Maintenance requires promptly treating spots and stains and should include routine, on-going care which reduces soil build-up on a fabric's surface.
- Do not rub or brush excessively or you may cause fuzzing. Any fuzz caused by the shorter fiber inherent to solution-dyed acrylic may be removed with a sweater shaver.

*NOTE: Use low temperature iron or steam to remove wrinkles.*

### HAND WASHING

- Soak fabric in a solution of 1/4 cup mild soap per gallon of lukewarm water.
- Use a sponge or a soft bristle brush to lightly agitate the stain.
- Rinse thoroughly to remove all soap residue.
- Allow fabric to air dry.

### MACHINE WASHING

Some drapery panels may be washed in the washing machine. Machine wash in cold water on the delicate cycle with normal amounts of mild laundry detergent. For severe mold or mildew, add 1 cup of bleach. Allow fabric to air dry.

### SPOT CLEANING

- Apply a light mist of mild soap and water using a spray bottle.
- Work the solution into the stain by lightly agitating the entire surface area of the fabric, moving from seam to seam, with a sponge or very soft bristle brush. Avoid scrubbing, and do not use a hard bristled brush or anything that will abrade the fabric.
- Rinse the entire fabric thoroughly to remove all soap residue.
- Blot excess moisture with a clean, soft towel or sponge.
- Blot or wet-vacuum excess water from the entire surface area of the fabric, moving from seam to seam.
- Air dry. Repeat rinsing and blotting until all soap residue is removed.

### OIL-BASED STAINS

Immediately apply an absorbent such as corn starch directly on the oil-based stain. Let sit for 10 minutes and remove the excess using a straight edge or ruler. This helps remove the stain and prevents it from being pressed into the fabric. Then proceed with the cleaning process.

### MOLD AND MILDEW STAINS

Thibaut Outdoor Performance Fabrics do not promote mildew growth, however, mildew may grow on dirt and other foreign substances that are not removed from the fabric. To clean stubborn stains:

- Prepare a solution of 1 cup of bleach and 1/4 cup mild soap per gallon of lukewarm water.
- Using a spray bottle, apply the cleaning solution to the entire area and allow to soak into the fabric for 15 minutes.
- Clean entire surface with a sponge, clean towel or very soft bristle brush.
- Rinse thoroughly to remove all soap residue.
- Allow fabric to air dry.
- It is best to clean the entire surface area of the fabric to avoid water rings and stains.